

TRIUMPH CONTAINERS



TRIUMPH

HYBRID PLASTIC CONTAINER WITH STEEL REINFORCEMENTS FOR MAXIMUM STRENGTH AND DURABILITY

- Weighs significantly less than same-size metal containers, improving worker safety
- Steel reinforcements strategically placed to support container, ensuring performance during heavy lifting
- Low maintenance never needs painting, is easy to clean, and is dent resistant

Industry standard

lids on all containers

UV resistant

for long term

1, 2, 3, & 4 yards

casters for easy

maneuverability

come with

exposure to

sunlight

- Comprehensive steel protection with electrophoretic coating (electro-coating) to maximize container life in corrosive environments
- Angled front fork pockets improve collection efficiency and reduce damage to container during emptying

11

• 100% recyclable

CAUTION

Polyethylene construction and sealed fasteners prevent leaking and maximize container life

Corrugation at sides and bottom add strength

Consistent wall thickness throughout improves performance

FEATURES



Coated Steel Pocket Guides are standard on all Triumph front load containers for added protection during fork entry. Pocket inside dimensions are maximum height. Pockets installed at a high point for easy fork entry.




Triumph Lifting Sleeves are captured by a molded-in ledge to bear the weight during lifting. On 6- and 8-yard containers, a two-inch structural tube supporting the bottom is attached to the lift pockets by side support brackets to manage heavier loads.



The 1¹/₂" Solid Steel Trunnion Bar on the Triumph Rear Load is supported with gussets to prevent damage when lifting heavy

loads.



Standard Oversized Washer reinforced with separate rubber washer prevents leakage at container base.





Oversized and Sealed Container Rim provides superior stiffness without trapping waste.

CUSTOMIZE YOUR CONTAINER

- Manual and Gravity lock options available on front load containers
- For additional customizations, contact your Area Manager





WHEEL FEATURES

- Reinforced caster mounting for • increased strength and durability
- Quick release caster plate allows for fast • caster replacement from outside the container.
- 4" caster plates prevent puncturing in container bottom and have single-bolt release
- Standard 6" casters on 1, 2, 3, & 4 vard containers
- Roll brakes available



AVAILABLE COLORS

The Triumph container is available in 6 standard colors. Standard frame color is black; standard lids are black and complement all container colors. Colors as shown in this document may differ slightly from the actual product.

















65 - Forest Green 68 - Dark Blue

63 - Brown

50 - Dark Gray

60 - Black



TRIUMPH



8 Yard FL **Slant** Top





6 Yard FL **Slant** Top



4 Yard FL







2 Yard FL



1 Yard FL

CONTAINER SPECIFICATIONS

MODEL	WIDTH	LOAD HEIGHT	MAX HEIGHT	DEPTH	LOAD RATING
8 YARD FL ST	81"	50"	82"	86"	5000 LBS.
6 YARD FL ST	81"	50"	68"	811⁄8"	3500 LBS.
4 YARD FL	81"	55¾"	71½"	58½"	2500 LBS.
3 YARD FL	81"	53¼"	62"	55"	1500 LBS.
2 YARD RL	78"	48¾"	50"	49¾"	1400 LBS.
1 YARD FL	81"	40¾"	421⁄8"	32"	700 LBS.

Container specifications vary slightly based on product mold. Height includes casters. Width includes lift pockets. Measurements reflect maximum dimensions.

Shipping information is estimated and varies slightly based on product mold and product

For maximum shipping capacity, some assembly is required: 8YD and 6YD containers ship with lids, lid rod, lid, rail and back cap inside of containers. 1YD, 2YD, 3YD and 4YD containers ship with lids inside of container.

location.

SHIPPING INFORMATION

MODEL	ASSEMBLY WEIGHT	STACK HEIGHT	T/L QTY (53' TRUCK)	LTL STACKING & LTL MAX QTY	LID DIMENSIONS (W X L)
8 YARD FL ST	552 LBS.	2 HIGH	7	1	36 x 58
6 YARD FL ST	530 LBS.	2 HIGH	14	1	36 x 58
4 YARD FL	403 LBS.	2 HIGH	20	2	36 x 58
3 YARD FL	373 LBS.	3 HIGH	33	4	36 x 54
2 YARD RL	300 LBS.	5 HIGH	85	6	31 x 49
1 YARD FL	217 LBS.	5 HIGH	115	9	36 x 32



Duramax Holdings LLC dba Otto Environmental Systems 12700 General Drive, Charlotte, North Carolina 28273 800-795-6886 • info@otto-usa.com • otto-usa.com © Duramax Holdings, LLC dba Otto Environmental Systems

